

It's a
dirty
job.

A roll-up-your-sleeves mud bath that takes
a tough person and an even tougher machine.

One that's field-tested every day and ready to get the job done without crying about the weather.

Chalk it up to a bucket load of innovations.

A quieter engine, an improved clutch, better cold starts

and a 48-volt electric model with E-Z-GO's Precision Drive System™

make the MPT the MVP on the job.

MPT 1200



MPT 1000



MPT 800

A
solid
work
record.

The Multi-Purpose Truck is the product of E-Z-GO's
fifty years of expertise. You can count on the MPT
when everyone else is counting on you.
Put it to the test. You'll love where it takes you.

MPT 800
(Gas or Electric)

MPT 1000
(Electric)

MPT 1200
(Gas)

GAS

Engines: 9.0 hp (6.7kW) rated, 4 cycle, 295 cc (18 ci) twin cylinder, air cooled
Lubrication: Pressurized oil system, washable permanent filter.
Battery: 12-volt maintenance free
Drive Train: Automatic, continuously variable transmission (CVT) forward and reverse
Fuel Tank: 6.0 gal (23L)
Speed: 12.5 - 13.5 mph (20-22 kph)

ELECTRIC

Motor: 36 volt DC high efficiency non-vented series wound
Drive Train: Direct motor shaft connected to transaxle pinion shaft
Batteries: Six, 6 volt heavy duty, deep cycle (107 minute, 220 amp-hour)
Charger: PowerWise™ fully automatic
Speed: 12.5 - 13.5 mph (20-22 kph)

Brakes:

Dual rear wheel self-adjusting mechanical drum brakes. Automatic park brake release with self-compensating system. Optional hydraulic front disc brakes

Suspension:

Heavy-duty leaf springs with hydraulic shock absorbers

Steering:

Rack and pinion

Weight:

800G: 780 lbs (355kg) dry / 800E: 675 lbs (305kg) without batteries

Length:

103 in (262cm)

Width:

47 in (119cm)

Height:

47 in (119cm) (top of steering wheel)

Ground Clearance:

5 in (at differential) (12.7cm)

Wheel Base:

66 in (168cm)

Front Wheel Tread:

38 in (97cm)

Rear Wheel Tread:

38 in (97cm)

Turning Clearance Diameter:

19 ft (5.8m)

Tires:

18 x 8.50 x 8 (4 ply rated)

Load Capacity:

800 lbs (360kg) including operator, passenger, accessories and cargo, 500 lbs (230kg) max. bed load

Cargo Bed Size:

44 in wide, 30.5 in long, 8-10.5 in deep (112cm x 78cm x 20-27cm)

Body:

Front: Flexible RIM plastic. Rear: Lightweight steel

Cargo Bed:

Rotomolded crosslink polyethylene. Hinged, removable tailgate

Chassis:

Tubular steel with E-Shield™

Additional Features:

Dash mounted key switch, reverse warning indicator, integral handgrip on hip restraints, manual forward/reverse selector

Dual rear wheel self-adjusting mechanical drum brakes. Automatic park brake release with self-compensating system. Optional hydraulic front disc brakes

Heavy-duty leaf springs with hydraulic shock absorbers

Rack and pinion

810 lbs (370kg) without batteries

111 in (282cm)

50 in (127cm)

47 in (119cm) (top of steering wheel)

5 in (at differential) (12.7cm)

77 in (196cm)

38 in (97cm)

38 in (97cm)

22 ft (6.7m)

18 x 8.50 x 8 (4 ply rated)

1,000 lbs (454kg) including operator, passenger, accessories and cargo; 600 lb (270kg) max. bed load

44.5 in wide, 36 in long, 12.5-15.5 in deep (115cm x 91cm x 32-40cm)

Front: Flexible RIM plastic. Rear: Lightweight steel

Rotomolded crosslink polyethylene. Hinged, removable tailgate

Tubular steel with E-Shield™

Dash mounted key switch, reverse warning indicator, integral handgrip on hip restraints, manual forward/reverse selector

Dual rear wheel self-adjusting mechanical drum brakes. Automatic park brake release with self-compensating system. Optional hydraulic front disc brakes

Heavy-duty leaf springs with hydraulic shock absorbers

Rack and pinion

860 lbs (390kg) dry

111 in (282cm)

50 in (127cm)

47 in (119cm) (top of steering wheel)

5 in (at differential) (12.7cm)

77 in (196cm)

38 in (97cm)

38 in (97cm)

22 ft (6.7m)

18 x 8.50 x 8 (4 ply rated)

1,200 lbs (540kg) including operator, passenger, accessories and cargo; 800 lb (360kg) max. bed load

44.5 in wide, 36 in long, 12.5-15.5 in deep (115cm x 91cm x 32-40cm)

Front: Flexible RIM plastic. Rear: Lightweight steel

Rotomolded crosslink polyethylene. Hinged, removable tailgate

Tubular steel with E-Shield™

Dash mounted key switch, reverse warning indicator, integral handgrip on hip restraints, manual forward/reverse selector

** Specifications subject to change without notice.